

In the Claims:

1. (Currently Amended) A method to provide feedback to an operator of a device ~~having feedback delay~~, comprising the steps of:

- (a) providing a device having a feedback delay;
- (b) displaying upon at least a portion of a display a first image of a view from the said device, the said device being at a first position;
- ~~((b))~~(c) issuing a movement command to cause a desired movement of the said device to a second position; and
- ~~((c))~~(d) displaying a second image of a predicted view from the said device at said second position prior to the operator receiving real feedback of said movement command, said second image occupying a portion of said display that is substantially identical to said portion of said display upon which said first image was displayed, said second image replacing said first image, said second image including at least a portion of said first image modified according to an operation selected from the group consisting of translation, rotation, magnification and reduction.

2. (Original) The method of claim 1, wherein said second image is based upon at least part of said first image.

3. (Original) The method of claim 2, wherein said second image includes a filler section outside of said at least part of said first image.

4. (Original) The method of claim 3, wherein said filler section includes a pattern.
5. (Original) The method of claim 4, wherein said filler section includes a repetitive pattern.
6. (Original) The method of claim 3, wherein said filler section includes historic image data of said predicted view.
7. (Currently Amended) The method of claim 1, further comprising the step of:
(((d))e) displaying a third image of an actual view from ~~the~~ said device at said second position.
8. (Currently Amended) The method of claim 1, further comprising the step of:
(((d))e) limiting said movement command to ensure that said second image can be based upon at least part of said first image.
9. (Original) The method of claim 1, wherein said step of issuing said movement command and said step of displaying said second image, occur substantially at the same time.
10. (Original) The method of claim 1, wherein said step of displaying said first image is performed by displaying said first image on a screen, said screen having a frame

disposed thereon, said first image being disposed substantially within said frame and wherein said step of displaying said second image is performed by displaying said second image on said screen such that, said second image includes substantially all image elements of said first image.

11. (Currently Amended) A feedback system for an operator of a device having a camera, comprising:

- (a) a device including a camera;
 - (b) a control arrangement configured for issuing a movement command to cause a desired movement of the said device from a first position to a second position;
- and

([[b]]c) a display configured for:

- (i) displaying, upon at least a portion of said display, a first image of a view from the said device, the said device being at a first position; and
- (ii) displaying a second image prior to the operator receiving real feedback of said movement command, said second image being a predicted view from the said device at said second position, said second image being based upon at least part of said first image, said second image occupying a portion of said display that is substantially identical to said portion of said display upon which said first image was displayed, said second image replacing said first image, said second image including at least a portion of said first image modified according to an operation selected from the group consisting of translation, rotation, magnification and reduction.

12. (Original) The system of claim 11, wherein said display is further configured for displaying a third image of an actual view from ~~the~~ said device at said second position.

13. (Previously Presented) The method of claim 3, wherein said filler section includes filler image data and wherein at least a portion of said filler image data is manipulated in a manner substantially corresponding to said movement command.

14. (Currently Amended) The ~~method~~ system of claim 11, wherein said second image is based upon at least part of said first image and wherein said second image includes a filler section outside of said at least part of said first image and wherein said filler section includes filler image data and wherein at least a portion of said filler image data is manipulated in a manner substantially corresponding to said movement command.

15. (New) The method of claim 1, wherein said device is a vehicle operative to be remotely controlled.

16. (New) The system of claim 11, wherein said device is a vehicle operative to be remotely controlled.